



Model 943-VM

Vacuum Relief Valve

BSBflamearrester.ie | BSBsystems.com

Visit our website for the most complete, up-to-date information

Drawing on extensive experience in the pressure safety management field, the BS&B FlameSaf® vacuum relief vent offers a dependable, internationally certified and precisely engineered design to prevent excessive vacuum build-up and implosion of valuable tankage during excess vacuum situations. The valve features a light-weight, compact design, are expertly engineered to respond to even minimal changes in vacuum. Consult your local BS&B representative or call us for consultation on your safety concerns.

Features

- Bottom-mount design
- Suitable for normal vacuum relief
- Complies with API 2000 Seventh Edition / EN ISO 28300
- Certified to ATEX – Directive 2014/34/EU
- Weight-loaded pallet design; intake from atmosphere
- Achieves full open (flowing pressure) at just 10% overvacuum
- Provides premium sealing with FEP diaphragms (metal-to-metal available for special requirements or higher settings)
- Leakage rates much tighter than API 2000/EN ISO 28300 requirements
- Screen protects valve internals from environment and contamination
- Pallet, seat & stem-guide made from stainless steel
- Modular design reduces requirements for inventory of spare parts
- Available in nom. diameter 2" – 12"



Model 943-VM
Vacuum Relief Valve



Flange Connection Type

- EN or DIN: ISO 7005-1
- JIS B 2220
- ASME B16.5

Valve Settings

- Vacuum: -2.5 to -70mbarg

Operating Conditions

- Maximum temperature rating up to 80% of ignition temperature of stored medium.

Protection

- Gas/air or vapour/air mixtures II 1/2 G Ex h IIB TX

Materials of Construction

	Carbon Steel	Stainless Steel	Others on request
Body	✓	✓	
Seat		✓	✓
Pallet		✓	✓
Diaphragm		✓	FEP
Seal	NBR, FPM, EPDM, FEP		✓

Limerick, Ireland

T: +353 61 517000
F: +353 61 309689
E: info@bsbflamearrester.ie

Düsseldorf, Germany

T: +49 211 930550
F: +49 211 3982171
E: info@bsb-systems.de

Houston, TX USA

T: +1 713 682 4515
F: +1 713 682 5992
E: sales@bsb-systems.com

Seoul, Korea

T: +82 2 3782 4591
F: +82 2 3782 4555
E: sales@bsb-systems.kr

Den Haag, Netherlands

T: +31 70 362 2136
F: +31 70 360 4724
E: info@bsb-systems.nl

Manchester, UK

T: +44 0 161 955 4202
F: +44 0 161 870 1086
E: sales@bsb-systems.co.uk

Shanghai, China

T: +86 21 6391 2299
F: +86 21 6391 2117
E: sales@bsb-systems.com

Products, specifications and all data in this literature are subject to change without notice. Questions regarding product selection and specifications for specific applications should be directed to BS&B. All sales are subject to the BS&B companies' standard terms and conditions of sale. Nothing herein should be construed as a warranty of merchantability or fitness for a particular purpose.